



Aluminium [AlMg 5]

Polerowany



Otwarte | kołnierz cylindryczny

Ø d	l		Indeks nr	Ø d _k	k	Ø d			
[mm]	[+0,5/-0]	[mm]		[+0/-0,5]	[mm]	[+0/-0,2]	[Nm]	[N]	[N]
M3	10,5	0,5-2,5	BS03AOCT25	7,0	0,9	4,9	2,0	2.000	700
Ø 5,0	11,5	2,5-3,5	35						
M4	11,0	0,5-3,0	BS04AOCT30	9,0	1,1	5,9	4,0	2.840	1.070
Ø 6,0	14,0	3,0-4,5	45						
M5	13,0	0,5-3,0	BS05AOCT30	10,0	1,1	6,9	5,0	4.900	1.170
Ø 7,0	16,0	3,0-5,5	55						
	19,0	5,5-8,0	80						
M6	16,0	0,5-3,0	BS06AOCT30	12,0	1,6	8,9	11,3	9.300	2.280
Ø 9,0	18,5	3,0-5,5	55						
	21,0	5,5-8,0	80						
M8	17,5	0,5-3,0	BS08AOCT30	15,0	1,6	10,9	14,6	14.700	2.450
Ø 11,0	20,0	3,0-5,5	55						
	22,5	5,5-8,0	80						
	25,0	8,0-10,5	105						
M10	19,0	0,5-3,0	BS10AOCT30	16,0	2,1	11,9	20,0	21.500	3.820
Ø 12,0	24,0	3,0-6,0	60						
	27,0	6,0-9,0	90						
	30,0	9,0-12,0	120						
M12	25,0	1,0-4,0	BS12AOCT40	22,0	2,1	15,9	23,0	27.400	4.400
Ø 16,0	28,0	4,0-7,0	70						
	31,0	7,0-10,0	100						

W ofercie nitonakrętki o niestandardowych wymiarach.