




Stal nierdzewna [A2]

Polerowany



Otwarte | kołnierz cylindryczny

Ø d	l [+0,5/-0]		Indeks nr	Ø d _k [+0/-0,5]	k ≤	Ø d [+0/-0,2]			
[mm]	[mm]	[mm]		[mm]	[mm]	[mm]	[Nm]	[N]	[N]
M4	11,0	0,5-3,0	BS04IOCT30	9,0	1,1	5,9	7,0	7.800	2.600
 Ø 6,0	14,0	3,0-4,5	45						
M5	13,0	0,5-3,0	BS05IOCT30	10,0	1,1	6,9	12,0	11.760	3.920
 Ø 7,0	16,0	3,0-5,5	55						
	19,0	5,5-8,0	80						
M6	16,0	0,5-3,0	BS06IOCT30	12,0	1,6	8,9	22,2	20.580	5.630
 Ø 9,0	18,5	3,0-5,5	55						
M8	17,5	0,5-3,0	BS08IOCT30	15,0	1,6	10,9	30,5	26.460	7.800
 Ø 11,0	20,0	3,0-5,5	55						
M10	19,0	0,5-3,0	BS10IOCT30	16,0	2,1	12,9	39,0	35.280	8.800
 Ø 13,0	24,0	3,0-6,0	60						

W ofercie nitonakrętki o niestandardowych wymiarach.